

3216B6



Rosi Code	3216B6														
Poles N°	2P+E			Current	16 A										
Voltage	200-250 V			Position	6 h										
Degree IP	67			Degree IK	8										
Thermal Stability	-25 /+70			Glow Wire	+650 / +850 Å°C										
Materials	Abs / Nylon / Rubber			Product dimensions	155X115X125 mm										
Weight Product	0,55 kg														
Poles	2														
Rated voltage insulation	690														
Rated voltage pulses	6														
Rated current	16														
Short circuit current	10														
Section min / max	1,5 - 10														
AC21	16A	AC21	690V	AC22	16A	AC22	690V	AC23	16A	AC23	500V	AC23	10A	AC23	690V
Standards	CEI EN 60309-1														
Standards	CEI EN 60309-2														
Standards	./														
Standards	./														
Mark CE	2014/35/UE														
Mark IMQ	./														
Mark ENEC 03	./														
Certified N°	./														

Ean Rosi Code	8033549920029		
Quantity	1		
Weight Product	0,55 kg		
Ean Rosi Code	8033549920029		
Package Quantity	1		
Weight Package	0,607 kg		
Ean Rosi Code	8033549920029		
Packaging Quantity	30		
Weight Packaging	18,83 kg		
Technical M.	Rosi Romano	Revision	1
		Date	1/6/14