

● Ball Lock Stainless Steel Cable Ties

- Self-locking head design speeds installation and locks into place at any length along tie body
- Provides a strong, durable method of cable bundling
- Can be used in a wide range of indoor, outdoor, and underground (including direct burial)
- Smooth surfaces and rounded edges assures cable protection and worker safety
- Provide the ultimate support for network cables
- Material:
 - 304 stainless steel for general-purpose applications
 - 316 stainless steel for the most corrosive environments
- Working (Operation) Temperature: -80°C - + 538°C (-112°F - + 1000°F)
- Min Installation Temperature: -60°C (-76°F)
- Any Length is available
- Water absorption: none
- Flammability: non-flammable
- Ultraviolet resistance: excellent, Chemical resistance: excellent
- UL (Underwriters Laboratories) : File E258930 based newest standard UL62275



Item No.	Size (mm)	Size (in)	Tensile Strength	Min Bundle Diameter (mm)	Max Bundle Diameter (mm)	Min Bundle Diameter (in)	Max Bundle Diameter (in)	UL Type	Series
LH-SS-S-125-5	4.6x125	5.0	890N(200lb)	15.00	38.00	0.59	1.49	2	S Series
LH-SS-S-150-6	4.6x150	6.0	890N(200lb)	15.00	46.00	0.59	1.81	2	
LH-SS-S-200-8	4.6x200	8.0	890N(200lb)	15.00	61.90	0.59	2.43	2	
LH-SS-S-260-10	4.6x260	10.0	890N(200lb)	15.00	81.00	0.59	3.19	2	
LH-SS-S-290-11	4.6x290	11.5	890N(200lb)	15.00	90.60	0.59	3.56	2	
LH-SS-S-360-14	4.6x360	14.0	890N(200lb)	15.00	112.80	0.59	4.44	2	
LH-SS-S-520-21	4.6x520	20.5	890N(200lb)	15.00	163.80	0.59	6.45	2	
LH-SS-S-680-27	4.6x680	27.0	890N(200lb)	15.00	214.80	0.59	8.45	2	
LH-SS-S-840-33	4.6x840	33.0	890N(200lb)	15.00	265.70	0.59	10.46	2	
LH-SS-H-200-8	7.9x200	8.0	1600N(350lb)	15.00	61.90	0.59	2.43	2	H Series
LH-SS-H-260-10	7.9x260	10.0	1600N(350lb)	15.00	81.00	0.59	3.19	2	
LH-SS-H-290-11	7.9x290	11.5	1600N(350lb)	15.00	90.60	0.59	3.56	2	
LH-SS-H-360-14	7.9x360	14.0	1600N(350lb)	15.00	112.80	0.59	4.44	2	
LH-SS-H-520-21	7.9x520	20.5	1600N(350lb)	15.00	163.80	0.59	6.45	2	
LH-SS-H-680-27	7.9x680	27.0	1600N(350lb)	15.00	214.80	0.59	8.45	2	
LH-SS-H-840-33	7.9x840	33.0	1600N(350lb)	15.00	265.70	0.59	10.46	2	
LH-SS-EH-290-11	12x290	11.5	2300N(500lb)	15.00	90.60	0.59	3.56	2	EH Series
LH-SS-EH-360-14	12x360	14.0	2300N(500lb)	15.00	112.80	0.59	4.44	2	
LH-SS-EH-520-21	12x520	20.5	2300N(500lb)	15.00	163.80	0.59	6.45	2	
LH-SS-EH-680-27	12x680	27.0	2300N(500lb)	15.00	214.80	0.59	8.45	2	
LH-SS-EH-840-33	12x840	33.0	2300N(500lb)	15.00	265.70	0.59	10.46	2	