

Leaders in Advanced Cable Installation Equipment

HOME . LATEST NEWS . JOBS @ CBS . FINDING US . CONTACT US
ABOUT US . PRODUCTS . SERVICES . CASE STUDIES . GLOBAL NETWORK

Duct Rods

A high quality fibreglass rod, specially constructed to provide exceptionally high tensile strengths, whilst retaining flexibility. The 80% fill rate glass fibre core is reinforced with a high strength resin. A braided reinforcing wrap is added before the final polypropylene wear resistant protective coating is applied. The continuous rods range from 4.5mm - 14mm with lengths from 30 metres - 300 metres.

Product No	Length	Weight	Cassette Diameter mm	Length mm	Width mm	Height mm	Min. Bend Radius mm	Breaking Strength kg
Mini Rod 4.5mm			400	400	162	520	140	770
B-101-030	30m	4.5kg						
B-101-050	50m	5.0kg						
B-101-060	60m	5.25kg						
B-101-070	70m	5.3kg						
B-101-080	80m	5.5kg						
Midi Rod 6.7mm			600	600	210	730	250	2500
B-102-060	60m	8.7kg						
B-102-080	80m	9.3kg						
B-102-100	100m	11kg						
B-102-150	150m	14kg						
Maxi Rod 9.0mm			800	850	520	940	310	3800
B-103-060-800	60m	26kg						
B-103-080-800	80m	30kg						
B-103-100-800	100m	33kg						
B-103-120-800	120m	35kg						
B-103-150-800	150m	36kg						
Maxi Rod 11mm			1000	1110	520	1130	390	6000
B-104-100-1000	100m	43kg						
B-104-150-1000	150m	45kg						
B-104-200-1000	200m	52kg						
B-104-250-1000	250m	59kg						
B-104-300-1000	300m	66kg						



Spare Rod is available for all models.
For example:- B-101-030-01 Spare Rod 30m



Rod Specification
Core Rod: E-Glass+Vinylester
Coating: Polypropylene, UV Stabilised