

| Specifications     |                      |                          |      |      |   |
|--------------------|----------------------|--------------------------|------|------|---|
| Function           | Max. Range           | Basic Accuracy           | 3385 | 3386 |   |
| Voltage DC         | 1000V                | $\pm(0.1\%+4d)$          | *    | *    |   |
| Voltage AC         | 1000V                | $\pm(1.0\%+3d)$          | *    | *    |   |
| Current DC         | 1000A                | $\pm(2.5\%+5d)$          |      |      | * |
| Current AC         | 1000A                | $\pm(2.5\%+5d)$          | *    | *    |   |
| Resistance         | 50MΩ                 | $\pm(3.0\%+5d)$          | *    | *    |   |
| Temperature        | 1000°C/ 1832°F       | $\pm(1.0\%+2.5°C/4.5°F)$ | *    | *    |   |
| Capacitance        | 5mF                  | $\pm(3.5\%+10d)$         | *    | *    |   |
| Frequency          | 10MHz                | $\pm(0.3\%+2d)$          | *    | *    |   |
| ACA flexible clamp | 3000A                | $\pm(2.8\%+8d)$          | *    | *    |   |
| Continuity check   | Buzzer sounds at 50Ω |                          |      |      |   |
| Diode test         | Test current 0.3mA   |                          |      |      |   |