



CP Plastic Series Ø 22 mm Push Buttons With Adapter (IP65)

- Functional specifications are maximized and adapter, which is facilitated to take apart easily.
- Sequential connectable body and contact blocks after lego logic.
- Contact blocks reliability with incombustible V0 PA6 body.
- Status follow up possibility by adding illumination unit.
- IP65 Protection degree with silicon band, finger ergonomic and aesthetic button.
- Protective cable inlet tips enabling maximum safety
- Minimum warm up, maximum life with protected LED's.
- Position facility with badge and label kits.
- Product variety fulfilling of all applications.

Technical Information

Mechanical Life	: 500.000 operations min.
Electrical Life	: 100.000 operations min.
Operating Temperature	: min./max. °C -5/+40
Protection Degree	: IP65
Operating Frequency	: Without load 3000 operations/hour At full load 1200 operations/hour
Rated Operating Voltage U_e	: 230 V AC
Rated Operating Current I_e	: 4 A
Insulation Voltage U_i	: 300 V
Stroke Resistance Voltage U_{imp}	: 2.5 kV
Standard Contact Material	: AgNi
Insulation Resistance	: 10 M Ω min. (500 V DC)
Dielectrical Strength	: Between body-contact 2000 V AC
	: Open contact 1500 V AC
Connection Cable Cross-Section Standard	: 1.5-2.5 mm ² : TS EN 60947-5-1 VDE0660

