

**Wall mounted socket**  
Part no. 5103A



- screw terminals
- switched
- mechanical DUO-interlock
- sockets can be padlocked

**Technical specifications**

|                           |                  |
|---------------------------|------------------|
| Ampere                    | 16 A             |
| Poles                     | 5 p              |
| Voltage                   | 400 V            |
| Clock position            | 6 h              |
| Hertz                     | 50-60 Hz         |
| Connection technology     | Screw terminals  |
| Contact                   | standard         |
| Protection type           | IP 44            |
| Enclosure material        | Plastic          |
| Weight                    | 1016 g           |
| Declaration of Conformity | DE, VDE, CN, CQC |

**Drawing**



| Drawing<br>1 MB 174 | Amp.<br>Poles   | 16            |      |      | 32            |      |      |
|---------------------|---|---------------|------|------|---------------|------|------|
|                     |   | 3             | 4    | 5    | 3             | 4    | 5    |
| Dim. in mm          | a   | 225           | 225  | 225  | 225           | 225  | 225  |
|                     | b   | 118           | 118  | 118  | 118           | 118  | 118  |
|                     | c   | 141           | 141  | 141  | 146           | 146  | 146  |
|                     | d   | 208           | 208  | 208  | 208           | 208  | 208  |
|                     | e   | 101           | 101  | 101  | 101           | 101  | 101  |
|                     | f   | 6.3           | 6.3  | 6.3  | 6.3           | 6.3  | 6.3  |
|                     | g   | 8             | 8    | 8    | 8             | 8    | 8    |
|                     | h   | 250           | 252  | 254  | 264           | 264  | 264  |
|                     | M   | 1x25 and 1x32 |      |      | 1x25 and 1x32 |      |      |
|                     | M*  | 2x25          | 2x25 | 2x25 | 2x25          | 2x25 | 2x25 |
|                     | Max. cable diam. (mm)   | 25            | 25   | 25   | 25            | 25   | 25   |
|                     | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1.5           | 1.5  | 1.5  | 2.5           | 2.5  | 2.5  |
|                     |   | -4            | -4   | -4   | -10           | -10  | -10  |