

W-Series
WPD 104 1x25+1x16/2x16+3x10 GY**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com**Power feed-in**

Our wide range of W-Series terminal blocks with our WPD main line branch terminals, which are optimised to guarantee both convenience and space gains, ensures a secure and convenient connection at the power feed-in.

General ordering data

Type	WPD 104 1x25+1x16/2x16+3x10 GY
Order No.	1562000000
Version	W-Series, Distribution block, Rated cross-section: Screw connection, Terminal rail / mounting plate
GTIN (EAN)	4050118367157
Qty.	1 pc(s).

W-Series
WPD 104 1x25+1x16/2x16+3x10 GY

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	33.3 mm	Width (inches)	1.311 inch
Height	68 mm	Height (inches)	2.677 inch
Depth	49 mm	Depth (inches)	1.929 inch
Net weight	96 g		

Temperatures

Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	130 °C
----------------------------------	--------	----------------------------------	--------

Material data

Material	Wemid	Colour	Grey
UL 94 flammability rating	V-0		

System specifications

Version	Screw connection	End cover plate required	No
Number of potentials	1	Number of levels	1
No. of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	Yes	PE connection	No
Mounting rail	TS 35	N-function	Yes
PE function	No	PEN function	No

Additional technical data

Installation advice	Terminal rail / mounting plate	Open sides	closed
Type of mounting	Snap-on		

Conductors for clamping (rated connection)

Connection direction	on side	Type of connection	Screw connection
----------------------	---------	--------------------	------------------

Rating data

Rated AC voltage	1,000 V AC	Rated DC voltage	1,000 V DC
Rated current	101 A	Current at maximum wires	101 A
Standards	IEC 60947-7-1, UL 1059		

UL rating data

Certificate No. (UR)	E60693	Current size B (UR)	85 A
Current size C (UR)	85 A	Voltage size B (UR)	600 V
Voltage size C (UR)	600 V	Wire cross section max. (UR)	4 AWG
Wire cross section min. (UR)	14 AWG		

Classifications

ETIM 5.0	EC001329	ETIM 6.0	EC000897
eClass 6.2	27-14-11-20	eClass 7.1	27-14-11-20
eClass 8.1	27-14-11-20	eClass 9.1	27-14-11-20

Data sheet**W-Series**
WPD 104 1x25+1x16/2x16+3x10 GY**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com**Technical data****Product information**

Product information Power distribution block (Bus Bar) also usable for distribution of neutral conductor and function earth.

Approvals

Approvals



ROHS Conform

Downloads

Approval/Certificate/Document of Conformity	DE_PT1001_20160419_004_ISSUE01.pdf
Brochure/Catalogue	CAT 1 TERM 16/17 EN
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP


Safety noteSafety notice [Safety Information](#)

Data sheet

W-Series
WPD 104 1x25+1x16/2x16+3x10 GY

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Drawings



Technical data

Inputs

Number of connections

Solid

Stranded

Flexible with ferrule

Ribbon cable

Torque

Clamping screw

Stripping length

Outputs

Number of connections

Solid

Stranded

Flexible with ferrule

Torque

Clamping screw

Stripping length

No. of poles

Note

IEC 60947-7-1, UL 1059

top	mid./left	mid./mid.	mid./right	bottom
-----	-----------	-----------	------------	--------

	1		1	
--	---	--	---	--

	2.5...25mm ²		1.5...16mm ²	
--	-------------------------	--	-------------------------	--

	2.5...25mm ²		1.5...16mm ²	
--	-------------------------	--	-------------------------	--

	1.5...16mm ²		1.5...10mm ²	
--	-------------------------	--	-------------------------	--

	2.5Nm		2.5Nm	
--	-------	--	-------	--

	M 6		M 6	
--	-----	--	-----	--

	19mm		19mm	
--	------	--	------	--

top	mid./left	mid./mid.	mid./right	bottom
-----	-----------	-----------	------------	--------

3				2
---	--	--	--	---

1.5...10mm ²				1.5...16mm ²
-------------------------	--	--	--	-------------------------

1.5...10mm ²				1.5...16mm ²
-------------------------	--	--	--	-------------------------

1.5...6mm ²				1.5...10mm ²
------------------------	--	--	--	-------------------------

2Nm				2.5Nm
-----	--	--	--	-------

M 5				M 6
-----	--	--	--	-----

12mm				14mm
------	--	--	--	------

1				
---	--	--	--	--