

Accessories
WKB 1/10

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

**Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General ordering data

| | |
|------------|---|
| Type | WKB 1/10 |
| Order No. | 1604330000 |
| Version | Accessories, Cross-connection slider, Cross-connector accessories, No. of poles: 10 |
| GTIN (EAN) | 4008190129576 |
| Qty. | 20 pc(s). |

Data sheet

Accessories WKB 1/10

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Width | 77.3 mm | Width (inches) | 3.043 inch |
| Height | 9.3 mm | Height (inches) | 0.366 inch |
| Depth | 6.1 mm | Depth (inches) | 0.24 inch |
| Net weight | 8.05 g | | |

Temperatures

| | | | |
|-----------------------------------|--------|----------------------------------|--------|
| Operating temperature range, max. | 100 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 100 °C | | |

Material data

| | | | |
|---------------------------|--------------|--------|--------|
| Material | Polyamide 66 | Colour | Orange |
| UL 94 flammability rating | V-2 | | |

System specifications

| | | | |
|---------|-----------------------------|---------------|------|
| Version | Cross-connector accessories | Mounting rail | none |
|---------|-----------------------------|---------------|------|

Additional technical data

| | | | |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | No | Installation advice | Direct mounting |
| Type of fixing | Plugged | Type of mounting | Clamped |

Dimensions

| | |
|-----------------|------|
| Pitch in mm (P) | 8 mm |
|-----------------|------|

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000489 | ETIM 4.0 | EC000489 |
| ETIM 5.0 | EC000489 | ETIM 6.0 | EC000489 |
| UNSPSC | 30-21-18-11 | eClass 5.1 | 27-14-11-45 |
| eClass 6.2 | 27-14-11-40 | eClass 7.1 | 27-14-11-40 |
| eClass 8.1 | 27-14-11-40 | eClass 9.0 | 27-14-11-40 |
| eClass 9.1 | 27-14-11-40 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|--------------------|--|
| Brochure/Catalogue | CAT 1 TERM 16/17 EN |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |