

Accessories
ZQV 4N/41 RT

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

**Spring connection with tension clamp Technology**

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| | |
|------------|------------------------------------|
| Type | ZQV 4N/41 RT |
| Order No. | 1794070000 |
| Version | Accessories, Cross-connector, 32 A |
| GTIN (EAN) | 4032248234141 |
| Qty. | 10 pc(s). |

Accessories
ZQV 4N/41 RT

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|----------|-----------------|------------|
| Width | 2.8 mm | Width (inches) | 0.11 inch |
| Height | 248.8 mm | Height (inches) | 9.795 inch |
| Depth | 25.7 mm | Depth (inches) | 1.012 inch |
| Net weight | 28.6 g | | |

Temperatures

| | | | |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -60 °C | Continuous operating temp., max. | 130 °C |
|----------------------------------|--------|----------------------------------|--------|

Material data

| | | | |
|---------------------------|-------|--------|-----|
| Material | Wemid | Colour | Red |
| UL 94 flammability rating | V-0 | | |

System specifications

| | | | |
|---------|-------------------|---------------|------|
| Version | For the terminals | Mounting rail | none |
|---------|-------------------|---------------|------|

Additional technical data

| | | | |
|---------------------|-----------------|----------------|---------|
| Installation advice | Direct mounting | Type of fixing | Plugged |
|---------------------|-----------------|----------------|---------|

Dimensions

| | |
|-----------------|--------|
| Pitch in mm (P) | 6.1 mm |
|-----------------|--------|

Rating data

| | |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000489 | ETIM 4.0 | EC000489 |
| ETIM 5.0 | EC000489 | ETIM 6.0 | EC000489 |
| UNSPSC | 30-21-18-01 | eClass 5.1 | 27-14-11-40 |
| eClass 6.2 | 27-14-11-40 | eClass 7.1 | 27-14-11-40 |
| eClass 8.1 | 27-14-11-40 | eClass 9.0 | 27-14-11-40 |
| eClass 9.1 | 27-14-11-40 | | |

Product information

| | |
|---------------------|---|
| Product information | Attention: not finger-safe; not suitable for ATEX use |
|---------------------|---|

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|--|
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
|------------------|--|