

**W-Series**  
**WPD 131 1X95/1X95 GY**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com



**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

Type	WPD 131 1X95/1X95 GY
Order No.	<a href="#">2503090000</a>
Version	W-Series, Distribution block, Rated cross-section: 95 mm <sup>2</sup> , Terminal rail / mounting plate
GTIN (EAN)	4050118516920
Qty.	2 Stück

## W-Series WPD 131 1X95/1X95 GY

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 1429-0  
Fax: +49 5231 14292083  
www.weidmueller.com

## Technische Daten

### Dimensions and weights

Width	25.5 mm	Width (inches)	1.004 inch
Height	93 mm	Height (inches)	3.661 inch
Depth	57 mm	Depth (inches)	2.244 inch
Net weight	96 g		

### Temperatures

Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C
----------------------------------	--------	----------------------------------	--------

### Material data

Material	Wemid	Colour	Light Grey
UL 94 flammability rating	V-0		

### System specifications

Version	Screw connection	Tightening torque (clamping screw for aluminium conductors)	22.6 Nm (10 undefined)
Tightening torque (clamping screw for copper conductors)	19 Nm (10 undefined)	End cover plate required	No
Number of potentials	1	Number of levels	1
No. of clamping points per level	2	Levels cross-connected internally	No
Mounting rail	TS 35		

### Additional technical data

Installation advice	Terminal rail / mounting plate	Type of mounting	Snap-on
---------------------	--------------------------------	------------------	---------

### Rating data

Rated cross-section	95 mm <sup>2</sup>	Rated voltage	1,000 V
Rated AC voltage	1,000 V AC	Rated DC voltage	1,000 V DC
Standards	IEC 60947-7-1, UL 1059, CSA	Rated impulse withstand voltage	8 kV
Pollution severity	3	Surge voltage category	III

### UL rating data

Certificate No. (UR)	E60693	Certificate No. (cURus)	E60693
Current size B (UR)	90 A	Current size C (UR)	90 A
Voltage size B (UR)	600 V	Voltage size C (UR)	600 V
Wire cross section max. (UR)	4 AWG	Wire cross section min. (UR)	14 AWG

### Classifications

ETIM 5.0	EC001329	ETIM 6.0	EC000897
eClass 6.2	27-14-11-20	eClass 7.1	27-14-11-20
eClass 8.1	27-14-11-20	eClass 9.1	27-14-11-20

### Product information

Product information	You will find additional information in the downloadsection of the onlinecatalogue
Descriptive text technical data	Rated current with Cu conductors: 232 A

**Datenblatt****W-Series**  
**WPD 131 1X95/1X95 GY****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 1429-0  
Fax: +49 5231 14292083  
www.weidmueller.com**Technische Daten****Approvals**

Approvals



ROHS

Conform

**Downloads**Approval/Certificate/Document of  
Conformity[CE declaration](#)

Engineering Data


[STEP](#)

User Documentation

[Additional Datasheet](#)**Safety note**

Safety notice

[Safety Information](#)

**Datenblatt****W-Series**  
**WPD 131 1X95/1X95 GY****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 1429-0  
Fax: +49 5231 14292083  
[www.weidmueller.com](http://www.weidmueller.com)**Zeichnungen**

## Technical data

### Inputs

Number of connections

Solid

Stranded

Flexible with ferrule

Ribbon cable

Torque

Clamping screw

Stripping length

### Outputs

Number of connections

Solid

Stranded

Flexible with ferrule

Torque

Clamping screw

Stripping length

Poles

### Note

IEC 60947-7-1, UL 1059, CSA

top	mid./left	mid./mid.	mid./right	bottom
		1		
		16...16mm <sup>2</sup>		
		16...95mm <sup>2</sup>		
		10...70mm <sup>2</sup>		
		19Nm		
		M 14		
		26mm		
top	mid./left	mid./mid.	mid./right	bottom
1		1		
1.5...10mm <sup>2</sup>		16...16mm <sup>2</sup>		
1.5...10mm <sup>2</sup>		16...95mm <sup>2</sup>		
1.5...6mm <sup>2</sup>		10...70mm <sup>2</sup>		
1.2Nm		19Nm		
M 4		M 14		
10mm		26mm		
1				

Rated current with Cu conductors: 232 A