


金属防水电缆接头M型 Metallic waterproof cable connector M type



CE SGS

- 产品材质: 黄铜镀镍, UL认可的尼龙 PA66
- 密封件: 丁晴橡胶(NBR), 耐候橡胶 (EPDM)
- 工作温度: -40℃至100℃, 瞬时耐热至 120℃
- 防护等级: IP68(旋紧部位)

- **Material:** Brass plated with nickel, nylon PA66 certified by UL
- **Weather strip:** Nitrile butadiene rubber (NBR), Weathering-resistance rubber (EPDM)
- **Working temperature:** -40℃ to 100℃, instantaneous heat resistance up to 120℃
- **Characteristics:** IP68(Rotate the part)



产品型号 Model	适用电缆 Cable Range (mm)	螺纹外径 Thread O. D. AG (mm)	螺纹长度 Thread Length GL (mm)	扳手直径 Spanner Size (mm)
M12 x 1.5	3-6.5	12	6	14
M16 x 1.5	4-8	16	7	17
M18 x 1.5	5-10	18	7	20
M20 x 1.5	6-12	20	7.5	22
M22 x 1.5	10-14	22	7.5	24
M24 x 1.5	11-15	24	8	26
M25 x 1.5	12-16	25	8	27
M25 x 1.5	13-18	25	8	30
M27 x 1.5(2)	13-18	27	8	30
M30 x 1.5(2)	15-20	30	9	33
M32 x 1.5(2)	16-21	32	9	35
M40 x 1.5(2)	22-32	40	9	45
M50 x 1.5(2)	32-38	50	10	57
M63 x 1.5(2)	37-44	63	11	68
M70 x 1.5(2)	42-52	70	15	80
M72 x 1.5(2)	42-52	70	15	80
M75 x 1.5(2)	42-52	75	15	80