


Metallic waterproof cable connector PG type



CE SGS

- 产品材质: 黄铜镀镍, UL认可的尼龙 PA66
- 密封件: 丁晴橡胶(NBR), 耐候橡胶 (EPDM)
- 工作温度: -40℃至100℃, 瞬时耐热至120℃
- 防护等级: IP68(旋紧部位)
- Material: Brass plated with nickel, nylon PA66 certified by UL
- Weather strip: Nitrile butadiene rubber (NBR), Weathering-resistance rubber (EPDM)
- Working temperature: -40℃ to 100℃, instantaneous heat resistance up to 120℃
- Characteristics: IP68(Rotate the part)



产品型号 Model	适用电缆 Cable Range (mm)	螺纹外径 Thread O. D. AG (mm)	螺纹长度 Thread Length GL (mm)	扳手直径 Spanner Size (mm)
PG7	3-6.5	12.5	6	14
PG9	4-8	15.2	7	17
PG11	5-10	18.6	7	20
PG13.5	6-12	20.4	7.5	22
PG16	10-14	22.5	7.5	24
PG19	11-15	24	8	26
PG21	13-18	28.3	8	30
PG25	16-20	30	9	33
PG29	18-25	37	9	40
PG36	22-32	47	9	50
PG42	32-38	54	10	57
PG48	37-44	59.3	11	64
PG63	42-52	72	15	80