

Presentation

With exclusive features, Denor WCT DIN rail contactor is definitely geared to absolute safety

Continuous safety for operators and unqualified personnel.

Compact design and modularization design

Rating :16, 20, 25, 40, 63 and 100 A

Number of poles: 1P, 2P, 3P, 4P

Coil Voltage: 24VAC, 110VAC, 220VAC, 380VAC,etc 50/60Hz

Compliance with standards: IEC/EN 61095 and CEI 1095

Electrical endurance (O-C): 100,000 cycles

Maximum number of switching operations a day: 100

Elegant appearance. Amounting instruction diagram is appended for convenient operation

No noise during operation

Utilization category: AC-1,AC-7a,AC-7b

2 versions: Standard contactors / Manually operated contactors

Optional auxiliary: Open-Close indication, interference filtering, dual control, time delay

Benefits

Easy to select, with a 1 to 4 poles wide range compliant with DIN standard

Peace of mind with the complete modular system

Flexible auxiliaries combination with a simple clip-on system

Applications


Control and monitoring of electrical circuits in all industrial, commercial and residential buildings.

Control and monitoring of single- or three-phase loads up to 100A.

interface between the control gear & power circuits for final circuits such as lighting, heating, roller blind, watering system,

ovens, utility motors: ventilation, heat pump etc.

Specifications

Type 1P	Rating(In) AC7a	AC7b	Control voltage (VAC)(50/60Hz)	Contact	In 18 mm modules	Denor code
	16A	6A	230	1NO	1	CT161NO
			230	1NC	1	CT161NC
	20A	6A	230	1NO	1	CT201NO
			230	1NC	1	CT201NC
	25A	8.5A	230	1NO	1	CT251NO
			230	1NC	1	CT251NC